

#### **DOMINATORPLUS**

# H3101 Hydrogen Gas Open Top Range

## **Key features**

- Energy efficient, high performance 5.5kW burners
  Hydrogen flame profile is better directed into pot so
  - Hydrogen flame profile is better directed into pot seensures increased efficiency and heat up times
- · Semi-sealed, pressed stainless steel hob
  - Easy to remove and keep clean
- Twin cast iron pan supports
  - Long-lasting and robust
- · Vitreous enamelled oven chamber
  - Easy to clean and to keep clean
- Wide oven temperature range of 120 270°C
  - Ideal to prepare a wide variety of food
- · Piezo ignition to oven
  - Simple, trouble-free operation
- Twin oven doors with individual catches
  - Retains heat within the oven chamber
- Oven has 5 shelf positions and allows 2 shelf cooking
  - Versatile, ideal for a wide range of menu items
- · Low profile door handles
  - Reduces intrusion into work space
- Laser-etched control icons
  - Permanent, indelible markings

#### Accessories

- · Fully integrated extended flue
- Splashplate and plateshelf (not for use with extended flue)
- Oven shelf
- · Lift-off fryplate
- Factory fitted, adjustable castors
- · Fixed installation kit

### Other Hydrogen Models


- H3860F twin basket fryer with filtration
- H3925 chargrill
- · H3641 smooth griddle
- H3532 salamander grill




### **DOMINATORPLUS**

### H3101

# Hydrogen Gas Open Top Range





Measurements in mm

Unit on castors is the same hob height

#### Installation notes

Adequate ventilation must be provided to supply sufficient fresh air for combustion and to allow easy removal of any such products that may present a risk to health. Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit, draught free position. If floor is made of a combustible material, local fire requirements must be checked to ensure compliance.

A clearance of 150mm should be observed between appliance and any combustible wall.

# Specification details

Total rating (kW - Nett)		38.5
Inlet size		3/4" BSP
Flow rate - (m³/hr)		13.58
Inlet pressure (mbar)		20
Operating pressure (mbar)		15
Hob burner rating (kW)		5.5 x 6
Oven burner rating (kW)		6.5
Oven dimensions (w x d x h - mm)		700 x 535 x 430
Oven shelf (w x d - mm)		700 x 535
Gastronorm compatibility		2/1
Weight (kg)		109
Packed weight (kg)		122
Packed dimensions (w x d x h - mm)		1000 x 1000 x 1100
GTIN numbers		
On Feet	On Castors	
5056466907440	5056466907457	